

# PurpleSeal Express

Single-use frac-plug deployment system



## Preassembled, run-ready, and disposable

The exclusive PurpleSeal Express™ system streamlines frac plug installation and eliminates wellsite redressing errors that cause costly presets and soft-sets. This system combines a PurpleSeal™ PS-C or PS-X frac plug with our exclusive patented RP Disposable Setting Tool®. The plug and setting tool are preassembled with connections thread-locked or torque-tightened to prevent back-off. Just remove the assembly from the shipping carton, insert a power charge, install a firing head/igniter, and make the assembly up to the gun string. No shear screws or set screws to install, no connections to tighten, no oil to add. After the tool strokes to set the frac plug, it automatically releases pressure before it is retrieved. At the surface, simply remove the setting tool from the gun string and set it aside for recycling. No disassembly, no inspection, no redressing.

### Features and Benefits

- Preassembly at the factory eliminates wellsite redressing errors
- Anti-preset shear screws in the setting tool prevent premature plug setting
- There is no pressure discharge at surface
- The compact, lightweight assembly can be handled by one person
- The short length allows additional guns for each stage

Casing size in.	Casing weight lb/ft	Plug pressure rating psi	Plug OD in.	Plug ID in.	Plug length in.	Assembly length in.	Assembly weight lb	Setting force of plug lbf	Maximum power charge pressure psi	PurpleSeal Express part number PS-C	PurpleSeal Express part number PS-X
4.50	11.6-15.1*	10,000	3.600	1.000	14.66	43.50	45	20,000	16,000**	0029087	0022722
5.00	23.2	9,000	3.600	1.000	14.66	43.50	45	20,000	16,000**	0029087	0022722
5.00	18.0	10,000	3.850	1.000	15.63	45.13	48	20,000	16,000**	0035000	0030354
5.50	17.0	8,000	4.380	1.250	16.66	53.70	100	25,000	12,000**	0038667	0038702
5.50	20.0-23.0	10,000	4.380	1.250	16.66	53.70	100	25,000	12,000**	0038667	0038702

\*Qualified in Q-125 casing. \*\*Wireline connections to setting tool must contain this pressure to set plug.



**REPEAT PRECISION**

repeatprecision.com

**John Billings**  
Permian Region  
940.249.2219

**Andrew Gammon**  
Permian Region  
512.964.7799

**Gilbert Rodriguez**  
Permian Region  
432.853.6637

**Adam Curry**  
Appalachia Region  
724.882.9816

**Todd Draegert**  
Rocky Mountains Region  
970.380.8633