

Net Bypass Rate (bpm) Past 3.600 in. / (91.44 mm) OD Plug in 4.500 in. / (114.3 mm) 15.10 lb/ft / (22.47 kg/m) Casing

Customer: \_\_\_\_\_  
 Well Name & No.: \_\_\_\_\_  
 Date: \_\_\_\_\_

		Line Speed																																																		
(ft/min)→		0	20	40	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	500	520	540	560	580	600	620	640	660	680	700	720	740	760	780	800	820	840	860	880	900	920	940	960	980	1000
(m/min)→		0	6	12	18	24	30	37	43	49	55	61	67	73	79	85	91	98	104	110	116	122	128	134	140	146	152	158	165	171	177	183	189	195	201	207	213	219	226	232	238	244	250	256	262	268	274	280	287	293	299	305

Blue = input  
 Black = output

Select from list:

Plug OD	3.600in_91.44mm
Casing OD	4.500in_114.30mm
Casing Weight	15.10lb/ft_22.47kg/m

Casing ID	97.18 mm	3.83 in
Casing Area	7417.32 mm <sup>2</sup>	11.50 in <sup>2</sup>
Plug Area	6566.93 mm <sup>2</sup>	10.18 in <sup>2</sup>
Bypass Area	850.39 mm <sup>2</sup>	1.32 in <sup>2</sup>

